

Mikrotik dostopna točka RB951UI-2HND

Kategorija: [Dostopne točke](#)
Dobavljivost: **Ni na zalogi**
Šifra: **89514**

Cena: 56,23€ ~~63,90€~~



(slika je simbolična)

Kratek opis

RB951Ui-2HnD je brezžični SOHO AP z novo generacijo procesorja Atheros in večjo procesorsko močjo. Ima pet vmesnikov Ethernet, en USB 2.0 vhod in 2,4 GHz 802.11 b/g/n brezžični AP z vgrajenimi antenami. Ima 600MHz CPU, 128 MB RAM-a in PoE izhodno funkcijo za vrata # 5 - lahko napaja druge naprave, sposobne za PoE, z enako napetostjo, kot je priključena na enoto. Največja obremenitev izhoda je 500mA.

Paket vsebuje RouterBOARD 951Ui-2HnD v plastičnem ohišju in napajalnik.

SPECIFIKACIJE:

Details		
Product code	RB951Ui-2HnD	
Architecture	MIPSBE	
CPU	AR9344	
CPU core count	1	
CPU nominal frequency	600 MHz	
Dimensions	113x138x29mm	
RouterOS license	4	
Operating System	RouterOS	
Size of RAM	128 MB	
Storage size	128 MB	
Storage type	NAND	
MTBF	Approximately 100'000 hours at 25C	
Tested ambient temperature	-20C +60C	

Suggested price	\$59.95	
Wireless capabilities		
Details		
Wireless 2.4 GHz Max data rate	300 Mbit/s	
Wireless 2.4 GHz number of chains	2	
Wireless 2.4 GHz standards	802.11b/g/n	
Antenna gain dBi for 2.4 GHz	2.maj	
Wireless 2.4 GHz chip model	AR9344	
Wireless 2.4 GHz generation	Wi-Fi 4	
Ethernet		
Details		
10/100 Ethernet ports	5	
Peripherals		
Details		
Number of USB ports	1	
USB Power Reset	Yes	
USB slot type	USB type A	
Max USB current (A)	1	
Powering		
Details		
Number of DC inputs	2 (PoE-IN, DC jack)	
DC jack input Voltage	8-30 V	
Max power consumption	24 W	
Max power consumption without attachments	7 W	
FAN count	Passive	
PoE in	Passive PoE	
PoE in input Voltage	8-30 V	
PoE-out		
Details		
PoE-out ports	Ether5	
PoE out	Passive PoE	
Max out per port output (input 18-30 V)	500 mA	
Max total out (A)	500 mA	
Certification & Approvals		
Details		
Certification	CE, FCC, IC, EAC, ROHS	
Wireless specifications		
2.4 GHz	Transmit (dBm)	Receive Sensitivity
6MBit/s	30	-96

54MBit/s	25	-80
MCS0	30	-96
MCS7	23	-78