

Mikrotik hAP ac³ usmerjevalnik

Kategorija: [Usmerjevalniki](#)

Dobavljivost: **predvidena dobava 01.09.2026**

Šifra: **110411**

Cena: 103,28€ ~~109,18€~~



(slika je simbolična)

Kratek opis

hAP ac³ je brezžični dvopasovni usmerjevalnik s 5 gigabitnimi Ethernet vrati in zunanji visoko ojačljivimi antenami za večjo pokritost!

Pozabite na neskončno iskanje popolnega usmerjevalnika in pomikanje skozi celo vrsto testov in specifikacij!

Mikrotik je ustvaril cenovno dostopno točko za dom, ki ima vse funkcije, ki jih boste morda potrebovali v prihodnjih letih!

Ali se vaš stari usmerjevalnik trudi doseči vsak kotiček vašega doma? Pozabite na to!

Vključene so zunanje visokozmogljive brezžične antene z izjemno pokritostjo. Odslej v vsaki sobi le močna in stabilna brezžična povezava!

S 5 gigabitnimi Ethernet vrati, 256 MB RAM-a in štirijedrnim CPU lahko hAP ac³ zadovolji tudi največja in najzahtevnejša gospodinjstva.

S podporo za PoE lahko napaja druge naprave. Na voljo sta 128 MB NAND in vhod USB, s katerimi lahko dodate dodaten prostor za shranjevanje.

Novo ohišje omogoča namestitev naprave navpično ali vodoravno. Vključen je tudi komplet za pritrditev na steno.

SPECIFIKACIJE:

Details		
Product code	RBD53iG-5HacD2HnD	
Architecture	ARM 32bit	
CPU	IPQ-4019	
CPU core count	4	
CPU nominal frequency	716 MHz	
Dimensions	251 x 129 x 39 mm	
RouterOS license	4	

Operating System	RouterOS	
Size of RAM	256 MB	
Storage size	128 MB	
Storage type	NAND	
MTBF	Approximately 100'000 hours at 25C	
Tested ambient temperature	-40°C to 70°C	
IPsec hardware acceleration	Yes	
Suggested price	\$99.00	
Wireless capabilities		
Details		
Wireless 2.4 GHz Max data rate	300 Mbit/s	
Wireless 2.4 GHz number of chains	2	
Wireless 2.4 GHz standards	802.11b/g/n	
Antenna gain dBi for 2.4 GHz	3	
Wireless 2.4 GHz chip model	IPQ-4019	
Wireless 2.4 GHz generation	Wi-Fi 4	
Wireless 5 GHz Max data rate	867 Mbit/s	
Wireless 5 GHz number of chains	2	
Wireless 5 GHz standards	802.11a/n/ac	
Antenna gain dBi for 5 GHz	5.maj	
Wireless 5 GHz chip model	IPQ-4019	
Wireless 5 GHz generation	Wi-Fi 5	
AC speed	AC1200	
Ethernet		
Details		
10/100/1000 Ethernet ports	5	
Number of 1G Ethernet ports with PoE-out	1	
Peripherals		
Details		
Number of USB ports	1	
USB Power Reset	Yes	
USB slot type	USB type A	
Max USB current (A)	1	
Powering		
Details		
Number of DC inputs	2 (DC jack, PoE-IN)	
DC jack input Voltage	12-28 V	
Max power consumption	30 W	
Max power consumption without attachments	12 W	
FAN count	Passive	
PoE in	Passive PoE	
PoE in input Voltage	18-28 V	

PoE-out		
Details		
PoE-out ports	Ether5	
PoE out	Passive PoE	
Max out per port output (input 18-30 V)	0.5 A	
Max total out (A)	0.5 A	
Certification & Approvals		
Details		
Certification	CE, FCC, IC, EAC, ROHS	
IP	IP20	
Other		
Details		
Mode button	Yes	
Wireless specifications		
2.4 GHz	Transmit (dBm)	Receive Sensitivity
1MBit/s	25	-100
11MBit/s	25	-94
6MBit/s	26	-96
54MBit/s	23	-78
MCS0	26	-96
MCS7	22	-73
5 GHz	Transmit (dBm)	Receive Sensitivity
6MBit/s	26	-96
54MBit/s	22	-80
MCS0	26	-96
MCS7	21	-75
MCS9	19	-70

Uradna stran proizvajalca: https://mikrotik.com/product/hap_ac3#fndtn-specifications