

## TP-LINK 8-Port 10/100Mbps namizno stikalo s 4 porti PoE

Kategorija: [Stikala](#)

Dobavljivost: **predvidena dobava 23.07.2026**

Šifra: **109744**

**Cena: 37,11€** ~~42,16€~~



(slika je simbolična)

## Kratek opis

### HARDWARE FEATURES

|                       |                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Interface             | 8 10/100Mbps RJ45 Ports<br>AUTO Negotiation/AUTO                                                       |
| Network Media         | 10BASE-T: UTP category<br>EIA/TIA-568 100Ω STP (m<br>100BASE-TX: UTP catego<br>EIA/TIA-568 100Ω STP (m |
| Fan Quantity          | Fanless                                                                                                |
| Power Consumption     | Maximum (PoE on): 60.2W<br>Maximum (PoE off): 3.2W                                                     |
| External Power Supply | External Power Adapter(                                                                                |
| PoE Ports (RJ45)      | Standard: 802.3 af comp<br>PoE Ports: Port1- Port4<br>Power Supply: 57W                                |
| Backbound Bandwidth   | 1.6Gbps                                                                                                |

## HARDWARE FEATURES

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| Mac Address Table        | 2K                                                       |
| Dimensions ( W x D x H ) | 6.7*3.9*1.1 in. (171*98*28mm)                            |
| Max Power Consumption    | 2.66(220/50Hz. no PD co<br>65.92(220/50Hz. with 57W PoE) |
| Max Heat Dissipation     | 9.08BTU/h(no PD connec<br>224.92BTU/h(with 57W P         |

## SOFTWARE FEATURES

|                     |                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------|
| Transmission Method | Store-And-Forward                                                                                 |
| Advanced Functions  | Compatible With IEEE 80<br>Priority Function<br>Mac Address Auto-Learn<br>IEEE802.3x Flow Control |

## OTHERS

|                  |                                                                                                        |
|------------------|--------------------------------------------------------------------------------------------------------|
| Certification    | FCC, CE, RoHS                                                                                          |
| Package Contents | TL-SF1008P, Power Adap                                                                                 |
| Consumption      | 2.3 watts (max. no PD co<br>59.3 watts (max. with 57W PoE)                                             |
| Environment      | Operating Temperature:<br>Storage Temperature: -4<br>Operating Humidity: 10%<br>Storage Humidity: 5%~9 |

Več na: <https://www.tp-link.com/se/business-networking/unmanaged-switch/tl-sf1008p/#overview>

## Tehnične Specifikacije

Hitrost: 10/100 Mbps