

TP-LINK Archer T2U Nano 600Mbps brežžična USB mrežna kartica

Kategorija: [Mrežne kartice](#)

Dobavljivost: **predvidena dobava 09.09.2026**

Šifra: **109748**

Cena: 9,69€ ~~11,02€~~



(slika je simbolična)

Kratek opis

WIRELESS FEATURES	
Wireless Standards	IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	5GHz 2.4GHz
Signal Rate	5GHz 11ac: Up to 433Mbps(dynamic) 11n: Up to 150Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz 11n: Up to 200Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)

WIRELESS FEATURES

Reception Sensitivity	5GHz
	11a 6Mbps: -90dBm
	11a 54Mbps: -73dBm
	11n HT20 MCS0: -89dBm
	11n HT20 MCS7: -70dBm
	11n HT40 MCS0: -86dBm
	11n HT40 MCS7: -67dBm
	11ac VHT80 MCS0: -82dBm
	11ac VHT80 MCS9: -56dBm
	2.4GHz:
	11b 1Mbps: -96dBm
	11b 11Mbps: -88dBm
	11g 6Mbps: -89dBm
	11g 54Mbps: -74dBm
	11n HT20 MCS0: -89dBm
	11n HT20 MCS7: -72dBm
	11n HT40 MCS0: -86dBm
	11n HT40 MCS7: -66dBm
Transmit Power	<20dBm (EIRP)
Wireless Modes	Ad-Hoc / Infrastructure mode
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Modulation Technology	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

OTHERS

Certification	CE, FCC, RoHS
Package Contents	AC600 Nano Wireless USB Adapter Archer T2U Nano
	Resource CD
	Quick Installation Guide
System Requirements	Windows 10/8.1/8/7/XP (32/64bits),
	Mac OS X 10.9-10.13
Environment	Operating Temperature: 0°C~40°C (32°F~104°F)
	Storage Temperature: -40°C~70°C (-40°F~158°F)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

HARDWARE FEATURES

Interface	USB 2.0
Dimensions (W x D x H)	15*7.1*18.6mm
Antenna Type	Omni Directional

Uradna stran proizvajalca: <https://www.tp-link.com/in/home-networking/adapter/archer-t2u-nano/>