

TP-LINK EAP225-Outdoor AC1200 MU-MIMO Gigabit zunanja/notranja dostopna točka



Kategorija: [Dostopne točke](#)

Dobavljivost: **predvidena dobava 05.08.2026**

Šifra: **58758**

Cena: 85,22€ ~~92,96€~~

(slika je simbolična)

Kratek opis

Podrobno o izdelku:

Šifra proizvođača	EAP225-OUTDOOR
EAN koda	1210002618519
Proizvođač:	TP-LINK
razprodaja	No
Postavitev dostopne točke:	notranja/zunanja
Frekvenca:	2.4GHz, 5GHz
Standard:	IEEE 802.11a/b/g/n/ac
Porti:	1x Gigabit Ethernet (RJ-45) priključek (podpira 802.3af PoE in Passive PoE)
Varnost:	SSID v VLAN Mapping, Rogue AP zaznavanje, odpora za 802.1x, brezžična izolacija med strankami, brezžično filtriranje Mac naslovov ...
Antena:	2.4GHz: 2x 3dBi; 5GHz: 2x 4dBi
Napajanje:	802.3af/A PoE; 24V Passive PoE (+4,5pins; -7,8pins. PoE adapter priložen)
Poraba:	10,5 W
Temperaturno območje:	delovna temperatura: -30 °C ~ 70 °C (-22 °F ~ 158 °F), temperatura skladiščenja: -40 °C ~ 70 °C (-40 °F ~ 158 °F)
Vlažnost:	delovna vlažnost: 10% ~ 90% brez kondenzacije, Vlažnost skladiščenja: 5% do 90% brez kondenzacije
Dimenzije:	215 x 46 x 27 mm

	gumb za ponastavitev vodotesno ohišje IP65 namestitev na drog ali steno (kompleti na namestitev priloženi) Hardware Watch Dog: da hitrost signala: 802.11ac: 5G:6.5 Mbps to 867Mbps(MCS0-MCS9,NSS = 1 to 2 VHT20/40/80) 2.4G:78Mbps to 300Mbps (MCS8-MCS9 VHT20/40, NSS=1 to 3) 802.11n: 6.5 Mbps to 300 Mbps (MCS0-MCS15, VHT 20/40) 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 5.5, 11Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps brežžične funkcije: Multiple SSIDs(Up to 16 SSIDs, 8 for each band) Enable/Disable Wireless Radio Automatic Channel Assignment Transmit Power Control (Adjust Transmit Power on dBm) QoS(WMM) MU-MIMO Airtime Fairness Beamforming Band Steering Load Balance Rate Limit Reboot Schedule Wireless Schedule Wireless Statistics based on SSID/AP/Client moč prenosa: CE: < 20 dBm (2.4GHz, EIRP), < 25 dBm(5GHz, EIRP) FCC: < 23 dBm (2.4 GHz), < 22 dBm (5GHz) upravljanje: Omada App Omada Cloud Controller Omada Controller Software Cloud Access Email Alerts Management MAC Access Control SNMP: v1, v2c System Logging Local/Remote Syslog SSH Web-based Management L3 Management Multi-site Management Management VLAN
Dodatno:	
Garancija	36 mesecev
Vsebina paketa:	AC1200 Wireless MU-MIMO Gigabit Indoor/Outdoor dostopna točka EAP225-Outdoor napajalni adapter komplet za namestitev