

[TP-LINK JetStream TL-SG2428P 28-port 24x gigabit PoE+ RJ45 4x Gigabit SFP Smart mrežno stikalo switch](#)

Kategorija: [Stikala](#)

Dobavljivost: **predvidena dobava 10.06.2026**

Šifra: **61847**

Cena: 347,31€ ~~378,88€~~



(slika je simbolična)

Kratek opis

Podrobno o izdelku:

Proizvajalčeva koda	SG2428P
EAN koda	6935364030650
Proizvajalec	TP-LINK
Namestitev:	rack / namizni
Vrsta stikala:	Managed
Standard:	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3az, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1p, IEEE 802.1x
Vmesniki:	24x 10/100/1000 Mbps RJ45, 4x Gigabit SFP
Zmogljivost:	prepustnost: 56 Gbps število paketov na sekundo: 41,7 Mpps
PoE:	24x 802.3at/af, do 250W skupno

Quality of Service

Support 802.1p CoS/DSCP priority
Support 8 priority queues
Queue scheduling: SP, WRR, SP+WRR
Port/Flow- based Rate Limiting
IPv6 QoS
Voice VLAN

L2 and L2+ Features

Static Routing
DHCP Relay
DHCP Server
IGMP Snooping V1/V2/V3
802.3ad LACP (Up to 8 aggregation groups, containing 8 ports per group)
Spanning Tree STP/RSTP/MSTP
BPDU Filtering/Guard
TC/Root Protect
Loopback detection
802.3x Flow Control
LLDP, LLDP-MED

VLAN

Supports up to 4K VLANs simultaneously (out of 4K VLAN IDs)
MAC/Protocol-based VLAN

Access Control List

L2/L4 package filtering
MAC ACL
IP ACL
Combined ACL
IPv6 ACL

Security

AAA
Port Security
DHCP Snooping
IP-MAC-Port Binding
IPv6-MAC-Port Binding
ARP Inspection
802.1x and Radius Authentication
SSH v1/v2

Programske funkcije: SSL v3/TLSv1.2
Broadcast/Multicast/Unknown-unicast Storm Control
Dos Defend
IPv6
Dual IPv4/IPv6 stack
Multicast Listener Discovery (MLD) Snooping
IPv6 neighbor discovery (ND)
Path maximum transmission unit (MTU) discovery
Internet Control Message Protocol (ICMP) version 6
TCPv6/UDPv6

IPv6 Applications

DHCPv6 Client
Ping6
Tracert6
Telnet (v6)
IPv6 SNMP
IPv6 SSH
IPv6 SSL
Http/Https
IPv6 TFTP

MANAGEMENT

Omada Apps

Centralized Management

Omada Cloud-Based Controller
Omada Hardware Controller (OC300)
Omada Hardware Controller (OC200)
Omada Software Controller
Cloud Access Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Management Features ? Web-based GUI and CLI management
SNMP v1/v2c/v3, compatible with public MIBs and TP-Link private MIBs
RMON (1, 2, 3, 9 groups)
CPU Monitoring
Port Mirroring
Firmware Upgrade: TFTP & Web
System Diagnose: VCT
SYSLOG & Public MIBS
Dual Image
EEE

Dimenzije: 440 × 220 × 44 mm
Garancija 24 mesecev
Vsebina paketa: TL-SG2428P, napajalni kabel, rackmount kit, gumijaste noge

Tehnične Specifikacije

Hitrost: 10/100/1000 Mbps + SFP 1.25 Gbps