

TP-link stikalo 24-port Gigabit 10/100/1000 TL-SG1024D

Kategorija: [Stikala](#)
Dobavljivost: **predvidena dobava 10.08.2026**
Šifra: **109734**



Cena: 86,84€ ~~98,69€~~

(slika je simbolična)

Kratek opis

24 portno stikalo v standardnem 48cm (19") rack jeklenem ohišju z nizko porabo energije je odlična rešitev za vaše poslovno omrežje.

- inovativna energetska učinkovita tehnologija prihrani do 25%
- podpora IEEE 802.3x nadzoru pretoka za Full Duplex način
- 48Gbps zmogljivost preklapljanja
- Auto-MDI/MDIX izniči potrebo po crossover kablích
- podpira MAC address auto-learning in auto-aging
- Plug and Play
- 10K Jumbo frame izboljša prenose velikih datotek
- namizna ali rack uporaba

V paketu: stikalo, napajalni kabel, kit za montažo v rack omaro, gumijaste noge

tehnični podatki:

HARDWARE FEATURES

Standards and Protocols Interface

Network Media

Fan Quantity

Power Supply

Dimensions (W x D x H)

IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x
24 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)
Fanless
100-240VAC, 50/60Hz
11.6*7.1*1.7 in. (294*180*44 mm)

HARDWARE FEATURES

Mounting	Rack Mountable
Max Power Consumption	13.08W(220V/50Hz)
Max Heat Dissipation	44.63BTU/h

PERFORMANCE

Switching Capacity	48Gbps
Packet Forwarding Rate	35.7Mpps
MAC Address Table	8K
Jumbo Frame	10KB
Green Technology	Yes
Transfer Method	Store-and-Forward

OTHERS

Certification	FCC, CE, RoHS
Package Contents	24-Port Gigabit Desktop/Rackmount Switch Power Cord Installation Guide Rackmount Kits Rubber Feet
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Spletna stran proizvajalca: https://www.tp-link.com/en/products/details/cat-5072_TL-SG1024D.html#overview

Tehnične Specifikacije

Ohišje: Vgradno
Hitrost: 10/100/1000 Mbps